



Model: Solatube 750 DS-O Open Ceiling (21 in/530 mm Daylighting System)


Project: _____ Location: _____ Type: _____

Product Specifications Appear in CSI Division 08, Section 08 62 23. For budgeting and quotations use only. Qty: _____

Model		Capture Zone				Transfer Zone		Delivery Zone										
<u>S</u>	<u>7</u>	<u>5</u>	<u>0</u>	<u>D</u>	<u>S</u>	-	<u>F</u>	<u>0</u>	<u>0</u>	-	<u>E</u>	<u>0</u>	<u>0</u>	-	<u>L</u>	<u>0</u>	<u>0</u>	<u>0</u>
1		2	2a	3		3a	4		4a	5		5a	6					

1 Model

750 DS-O SolaMaster® Solatube 750 DS-O (21 in/530 mm Daylighting System)
Open Ceiling



Capture Zone

2 Dome






- DA** Acrylic Dome **DAI** Acrylic Outer Dome + Acrylic Inner Dome
- DPI** Acrylic Outer Dome + Polycarbonate Inner Dome (Required for High Velocity Hurricane Zones)

2a Dome Options (Leave blank if not desired)

- B** Security Bar **PB** Dome Edge Protection Band
- SK** Dome Security Kit*

* Inner dome required for Dome Security Kit

3 Flashings

- | | | | | | |
|--|---|-----------------------------------|---|------------------------------------|---|
| F4 4-inch
Self Mounted |  | F8 8-inch
Self Mounted |  | F11 11-inch
Self Mounted |  |
| FC Curb Cap
(Curb by Others) |  | FSM Metal Roof
Flashing |  | | |

3a Flashings Options (Leave blank if not desired)

- T12*** Roof Flashing Turret Extension 12 in/300 mm
- T24*** Roof Flashing Turret Extension 24 in/600 mm
- T36*** Roof Flashing Turret Extension 36 in/900 mm
- T48*** Roof Flashing Turret Extension 48 in/1200 mm
- FI** Flashing Insulator


* Specify additional extension tubes in #4

Transfer Zone

4 Extension Tubes Required*

Run measured from top of flashing to diffuser along centerline of tubing.

- | | |
|---|--|
| E1** One Extension Tube – Max Run = 24" | E7** Seven Extension Tubes – Max Run = 156" |
| E2** Two Extension Tubes – Max Run = 46" | E8** Eight Extension Tubes – Max Run = 178" |
| E3** Three Extension Tubes – Max Run = 68" | E9** Nine Extension Tubes – Max Run = 200" |
| E4** Four Extension Tubes – Max Run = 90" | E10** Ten Extension Tubes – Max Run = 222" |
| E5** Five Extension Tubes – Max Run = 112" | EXX** Total Run Length to be Determined by Bidding Contractor |
| E6** Six Extension Tubes – Max Run = 134" | |



*At least one 24" extension tube required for diffuser

**Compatible with dome ring to be used as a top tube or extension tube

***Total tube run will vary depending on flashing used

4a Options (Leave blank if not desired)

- | | |
|---|--|
| A1 One 0-90 Degree Extension Tube (Angle Adapter) | AK 16" Top Tube Angle Adapter and 16" Bottom Tube Angle Adapter |
| A2 Two 0-90 Degree Extension Tubes (Angle Adapter) | TA 16" Top Tube Angle Adapter |
| E Wire Suspension Kit (50 ft.) | R Trim Ring |

Delivery Zone

5 Diffuser Lens

- | | |
|--|--|
| L1 OptiView® Diffuser  | L2 Prismatic Diffuser  |
|--|--|

5a Options (Leave blank if not desired)

- D** Daylight Dimmer™

6 Measurement Standard

- M** Metric **I** Imperial

Accessories (Order separately.)

- SW** Low voltage switch (white) required to operate Solatube Daylight Dimmers. Note: Only one switch is required per ten (10) synchronously controlled dimmers.
- CA** Two Conductor Low Voltage Cable (500 ft.)

Example

750 DS-O-DPI-F8-E2-L1-M

SolaMaster Series® 750 DS-O (21 in/530 mm Daylighting System), Acrylic Outer Dome + Polycarbonate Inner Dome, 8-inch High Self Mounted Flashing, Two Extension Tubes and OptiView® Diffuser. For metric installations.